


Periscreen-M™ Machine Screen

Efficiently removes impurities
and deflocculates the stock
ahead of the headbox

*High capacity screening
for all stock types and
applications*



Periscreen-M Machine Screen

High Capacity Screening

The Periscreen-M machine screen is a high-capacity machine screen for all stock types and applications. The design is optimized to maximize efficiency and flow while serving as a protection screen effectively removing remaining impurities and deflocculating the stock prior to entering the headbox.

Low Pulse Design

The Periscreen-M machine screen is virtually pulsation-free and, in combination with the excellent deflocculation effect, promotes good formation and low MD and CD variations.

Designed with Latest Fluid Dynamics Technology

All flows through the Periscreen-M machine screen are simulated using advanced Computational Fluid Dynamics (CFD) technology to optimize operating conditions. This has led to the design of a machine screen that combines modern design and functionality that addresses the need for high-performance, cost-effective screening.

Reliable Operation at High Capacities

The optimized fluid dynamics of the Periscreen-M machine screen lead to stable flow and uniform impact on the screen cylinder. The specially-designed rotating foils deflocculate the stock to keep the screen cylinder "plug-free" and promote smooth operation at high hydraulic capacity.

For all stock types and applications

Benefits



Low power consumption

Optimized and functional design ensures low energy consumption at high operational reliability



High separation efficiency

Reduces contaminants in the final product



Stable flow conditions

For high capacity screening at maximum availability



Low maintenance costs

Durable design means low maintenance and maximum uptime



Trouble-free operation

Smooth performance at high capacities




Optimized process

Improves formation and sheet quality



Periscreen-M machine screen installation

Customized design



Dimensions

This easily installed, compact unit is available in different models.

Model Size	Screening Area m ²	Stock Inlet Diameter d ₁		Accept Diameter d ₂		Reject Diameter d ₃	
		mm	in	mm	in	mm	in
400S	0.26	200	8	200	8	80	3
400	0.39	200	8	200	8	80	3
500	0.64	250	10	250	10	80	3
630	1.01	300	12	300	12	100	4
800	1.65	400	16	400	16	150	6
1000	2.70	500	20	500	20	200	8
1250	4.15	600	24	600	24	200	8
1400	5.31	700	28	700	28	250	10
1600	6.58	700	28	700	28	250	10
1800	8.21	800	32	800	32	300	12
2000	10.74	900	36	900	36	300	12

Models 400S – 800 can be equipped with an optional reject dilution connection.
Periscreen-M screen cylinders are available with either slots or holes.

Specifications and information subject to change without notice.
General dimensions and not certified for construction or installation.


Optimized rotor design



Customized rotor design according to application and requirements.



Rotor foil designs are simulated to optimize screening efficiency.



Stable Flow Conditions

The unique design, combining an optimal rotor, a conical housing section, and a sloped accept chamber, improves the flow distribution throughout the entire screening zone. This results in a high capacity machine screen with maximum availability.

Improve your product quality

The Periscreen-M machine screen provides a uniform velocity profile and an evenly distributed stock suspension at the headbox. As a result, improved formation and enhanced sheet quality is achieved.

Certified Parts and Service 24 Hour Hotline for North America: 1-800-448-5422

Efficient, compact footprint with advanced design features



Optimal, customized rotor design



Conical housing section




Sloped accept chamber



Optimized accept outlet design and location

The Kadant Black Clawson Foundations product line offers a full range of fiber processing equipment and services.



For patent information about this and other Kadant products visit <https://kadant.com/en/patents>

KADANT

fiberprocessing.kadant.com Kadant is a global supplier of high-value, critical components and engineered systems used in process industries worldwide.

North America, Central America, and Japan:

Kadant Black Clawson LLC
1425 Kingsview Drive
Lebanon, OH 45036 USA
Tel: +1-513-229-8100
Email: info@kadant.com

China, Taiwan, and South Korea:

Kadant Fiberline (China) Co. Ltd.
STE 1960, Beijing Sunflower Tower
37 Maizidian Street, Chaoyang
District, Beijing 100125 China
Phone: +86-10-65813011/12/13
Email: Marketing.KFC@kadant.com

EMEA, APAC, and South America:

Kadant Lamort SAS
39, rue de la Fontaine Ludot,
B. P. 30046
Vitry-le-Francois cedex 51302
Phone: +33-26-74-80-80
Email: kadant.lamort@kadant.com

Kadant Noss AB
Malmgatan 25
602 23 Norrköping, Sweden
Phone: +46-(0)-11-23-15-00
Email: info.kadantnoss@kadant.com

Periscreen-M Machine Screen
©2024 Kadant Inc
01/2024